

ICE catheter

Features and specifications

_ \/	er'	ı 🗸 1	σ	nt	ப	ro
v	CI	J	5	ıιι		ıv

Catalog number	VSICE3D		
Outer diameter	9F		
Minimum sheath size	10F		
Working length	90 cm		
Articulating segment length	7.5 cm		
Fixed distal tip length	2 cm		
Deflection range	120°		
Compatibility	EPIQ 7C, EPIQ CVx, EPIQ CVxi		
Broadband frequency range	4 - 10 MHz		
Type of array	xMATRIX		
Number of elements	840		
Field of view	90°		
Volume field of view	90°x90°		
Imaging modes			
2D imaging	Υ		
Live 3D echo (3D Volume imaging, Live 3D Color Flow imaging)	Υ		
Spectral Doppler (PW/CW)	Υ		
iRotate echo (digital steering)	Υ		
Live xPlane imaging	Υ		

Compatible with Patient Interface Module (PIM) 2.4m (8.2-ft) in length

Indications for use

The VeriSight Pro ICE catheter is intended for intracardiac and intra-luminal visualization of cardiac and great vessel anatomy and physiology as well as visualization of other devices in the heart The catheter is intended for imaging guidance only, not treatment delivery, during cardiac interventional percutaneous procedures

Philips

3721 Valley Centre Drive, Suite 500, San Diego, CA 92130 USA www.philips.com/IGTdevices

©2020 Koninklijke Philips N.V. All rights reserved. Approved for external distribution D057587-00 092020